

Hydraulic Compactor
液压夯

Straight check valve, one-way unloading of the pump body pressure ensure the normal operation of the motor.

直通单向阀,单向卸载马达泵体压力,保证马达正常工作。

The conjunction of the flow control valve and relief valve can adjust the flow within the appropriate flow range to ensure the speed of vibration, can be suitable for excavators with different flow rates.

流量调节阀与溢流阀配合,可在适当的流量区间内调节流量,保证打击速度,可适配不同流量的挖机。

High strength vibration plate can ensure the service life time of hydraulic compactor.

高强度振动板,保证振动夯的使用寿命。

Imported motor improves the service life time and stability of power box body.

采用进口马达提高了动力箱的使用寿命和稳定性。

The adoption of high elastic rubber damper can reduce excavator resonance and increase equipment service life time.

采用高弹性橡胶减震胶块,弹性好,减少挖机共振,增加设备使用寿命。



Specifications 技术参数

FVC02

FVC03

FVC04

Outline Dimension 外形尺寸	A	617 mm	780 mm	780 mm
	B	760 mm	1135 mm	1135 mm
	C	420 mm	550 mm	550 mm
	D	PF1/2"	PF1/2"	PF1/2"
Total Weight	重量	192 kg	380 kg	550 kg
Working Pressure	工作压力	40~100 bar	80~120 bar	90~130 bar
Punch	打击力	25 kN	35 kN	40 kN
Working Flow	工作流量	30~50 lpm	50~70 lpm	60~80 lpm
Vibration Frequency	振动频次	2700 Vpm(max)	2700 Vpm(max)	2000 Vpm(max)
Suitable Carrier	适配挖机	1-3 ton	4-6 ton	7-10 ton

Specifications 技术参数

FVC06

FVC08

FVC10

Outline Dimension 外形尺寸	A	942 mm	1076 mm	1076 mm
	B	1246 mm	1620 mm	1620 mm
	C	750 mm	900 mm	900 mm
	D	PF3/4"	PF1"	PF1"
Total Weight	重量	870 kg	1180 kg	1300 kg
Working Pressure	工作压力	100~140 bar	150~180 bar	150~180 bar
Punch	打击力	80 kN	150 kN	160 kN
Working Flow	工作流量	80~120 lpm	100~170 lpm	120~210 lpm
Vibration Frequency	振动频次	2000 Vpm(max)	2000 Vpm(max)	2000 Vpm(max)
Suitable Carrier	适配挖机	11-16 ton	17-23 ton	24-35 ton

Outline Dimension 外形尺寸

